

LGPL

LGPLN
(Without Tap)

30, 16, 42, 20, 12, 26, 26, 26, 42(D)/f6 (Hole diameter H7), #4 (For bottom dead center lock), #18, #11, M10, 25, 20, 10, 7, L, S (Travel), 25, 5, #10, #26, #27

* Area to be induction hardened (Hatched Area)
* f6 $(\begin{smallmatrix} -0.025 \\ -0.041 \end{smallmatrix})$

Table of Components

No.	Description	Qty	Material and Remark
①	Slide Pin	1	Prehardened Steel HRC30 to 35
②	Stopper	1	S45C HRC50~
③	Coil Spring	1	SWOSC-V TR26

Slide pin (①)

Catalog No.	D	S
LGPLP (For LGPL)	42	40
LGPLNP (For LGPLN)	42	60



Order

Catalog No.	D	-	S
LGPLNP	42	-	40

Stopper (②)

Catalog No.	D
LGPT	42



Order

Catalog No.	D
LGPT	42

F	L	Coil Spring			Catalog No.	D	S
		Type	Initial Load(N)	Final Load(N)			
70	90	TR26-125	97	355	LGPL	42	40
90	110	TR26-175	115	392	LGPLN	42	60



Order

Catalog No.	D	-	S
LGPL	42	-	60