

2024/6/7

SANKYO OILLESS INDUSTRY, INC.

Page	Product	Wrong	Correct																																
239	BPSB BPSA BPSR BPSE	Travel S 11.2	Travel S 16																																
		■Spring Specification <table><tr><th>Catalog No.</th><th>D</th><th>Punch Length</th><th>Travel S</th></tr><tr><td rowspan="2"></td><td rowspan="2">10</td><td>80</td><td>12</td></tr><tr><td>90</td><td>11.2</td></tr><tr><td rowspan="2">BPSB BPSA BPSR BPSE</td><td rowspan="2">13</td><td>80</td><td>12</td></tr><tr><td>90</td><td>11.2</td></tr><tr><td></td><td>16</td><td>90</td><td>11.2</td></tr></table>	Catalog No.	D	Punch Length	Travel S		10	80	12	90	11.2	BPSB BPSA BPSR BPSE	13	80	12	90	11.2		16	90	11.2	<table><tr><td rowspan="5">BPSB BPSA BPSR BPSE</td><td></td><td>90</td><td>11.2</td></tr><tr><td rowspan="2">13</td><td>80</td><td>12</td></tr><tr><td>90</td><td>11.2</td></tr><tr><td>16</td><td>90</td><td>16</td></tr></table>	BPSB BPSA BPSR BPSE		90	11.2	13	80	12	90	11.2	16	90	16
		Catalog No.	D	Punch Length	Travel S																														
			10	80	12																														
				90	11.2																														
BPSB BPSA BPSR BPSE	13	80	12																																
		90	11.2																																
	16	90	11.2																																
BPSB BPSA BPSR BPSE		90	11.2																																
	13	80	12																																
		90	11.2																																
	16	90	16																																
	*1 Pierce entry is set at 5 mm.		*1 Pierce entry is set at 5 mm.																																