

2024/6/7

三協オイルレス工業株式会社

ページ	品名	誤	正																																																																																																																																																																																																																					
1260	USWA, USWAT	野線位置	<table><tr><th rowspan="3">Catalog No.</th><th>外径</th><th>長さ</th><th colspan="4">S=Lx15%</th><th colspan="4">S=Lx25%</th><th colspan="2">内径</th></tr><tr><th rowspan="2">D</th><th rowspan="2">L</th><th rowspan="2">S</th><th colspan="2">F kN</th><th rowspan="2">S</th><th colspan="2">F kN</th><th rowspan="2">V</th><th rowspan="2">d</th></tr><tr><th>初回</th><th>30万</th><th>初回</th><th>30万</th></tr><tr><td rowspan="4">30</td><td>30</td><td>4.5</td><td>1.2</td><td>1.1</td><td>7.5</td><td>2.5</td><td>2.4</td><td rowspan="4">36</td><td rowspan="4"></td></tr><tr><td>40</td><td>6.0</td><td>2.0</td><td>1.3</td><td>10</td><td>2.9</td><td>2.6</td></tr><tr><td>50</td><td>7.5</td><td>2.2</td><td>1.5</td><td>12.5</td><td>3.0</td><td>2.9</td></tr><tr><td>60</td><td>9.0</td><td>2.2</td><td>1.4</td><td>15</td><td>3.3</td><td>3.0</td></tr><tr><td rowspan="4">40</td><td>40</td><td>6.0</td><td>4.4</td><td>3.0</td><td>10</td><td>6.4</td><td>5.8</td><td rowspan="4">48</td><td rowspan="4">14</td></tr><tr><td>50</td><td>7.5</td><td>4.6</td><td>3.1</td><td>12.5</td><td>6.6</td><td>6.0</td></tr><tr><td>60</td><td>9.0</td><td>4.4</td><td>2.9</td><td>15</td><td>6.6</td><td>6.0</td></tr><tr><td>80</td><td>12.0</td><td>3.8</td><td>2.6</td><td>20</td><td>6.1</td><td>5.8</td></tr><tr><td rowspan="2">50</td><td>50</td><td>7.5</td><td>6.6</td><td>5.0</td><td>12.5</td><td>10.8</td><td>9.7</td><td rowspan="2"></td><td rowspan="2"></td></tr><tr><td>60</td><td>9.0</td><td>6.8</td><td>4.7</td><td>15.0</td><td>10.2</td><td>9.2</td></tr></table>	Catalog No.	外径	長さ	S=Lx15%				S=Lx25%				内径		D	L	S	F kN		S	F kN		V	d	初回	30万	初回	30万	30	30	4.5	1.2	1.1	7.5	2.5	2.4	36		40	6.0	2.0	1.3	10	2.9	2.6	50	7.5	2.2	1.5	12.5	3.0	2.9	60	9.0	2.2	1.4	15	3.3	3.0	40	40	6.0	4.4	3.0	10	6.4	5.8	48	14	50	7.5	4.6	3.1	12.5	6.6	6.0	60	9.0	4.4	2.9	15	6.6	6.0	80	12.0	3.8	2.6	20	6.1	5.8	50	50	7.5	6.6	5.0	12.5	10.8	9.7			60	9.0	6.8	4.7	15.0	10.2	9.2	<table><tr><th rowspan="3">Catalog No.</th><th>外径</th><th>長さ</th><th colspan="4">S=Lx15%</th><th colspan="4">S=Lx25%</th><th colspan="2">内径</th></tr><tr><th rowspan="2">D</th><th rowspan="2">L</th><th rowspan="2">S</th><th colspan="2">F kN</th><th rowspan="2">S</th><th colspan="2">F kN</th><th rowspan="2">V</th><th rowspan="2">d</th></tr><tr><th>初回</th><th>30万</th><th>初回</th><th>30万</th></tr><tr><td rowspan="4">30</td><td>30</td><td>4.5</td><td>1.2</td><td>1.1</td><td>7.5</td><td>2.5</td><td>2.4</td><td rowspan="4">36</td><td rowspan="4"></td></tr><tr><td>40</td><td>6.0</td><td>2.0</td><td>1.3</td><td>10</td><td>2.9</td><td>2.6</td></tr><tr><td>50</td><td>7.5</td><td>2.2</td><td>1.5</td><td>12.5</td><td>3.0</td><td>2.9</td></tr><tr><td>60</td><td>9.0</td><td>2.2</td><td>1.4</td><td>15</td><td>3.3</td><td>3.0</td></tr><tr><td rowspan="4">40</td><td>40</td><td>6.0</td><td>4.4</td><td>3.0</td><td>10</td><td>6.4</td><td>5.8</td><td rowspan="4">48</td><td rowspan="4">14</td></tr><tr><td>50</td><td>7.5</td><td>4.6</td><td>3.1</td><td>12.5</td><td>6.6</td><td>6.0</td></tr><tr><td>60</td><td>9.0</td><td>4.4</td><td>2.9</td><td>15</td><td>6.6</td><td>6.0</td></tr><tr><td>80</td><td>12.0</td><td>3.8</td><td>2.6</td><td>20</td><td>6.1</td><td>5.8</td></tr><tr><td rowspan="2">50</td><td>50</td><td>7.5</td><td>6.6</td><td>5.0</td><td>12.5</td><td>10.8</td><td>9.7</td><td rowspan="2"></td><td rowspan="2"></td></tr><tr><td>60</td><td>9.0</td><td>6.8</td><td>4.7</td><td>15.0</td><td>10.2</td><td>9.2</td></tr></table>	Catalog No.	外径	長さ	S=Lx15%				S=Lx25%				内径		D	L	S	F kN		S	F kN		V	d	初回	30万	初回	30万	30	30	4.5	1.2	1.1	7.5	2.5	2.4	36		40	6.0	2.0	1.3	10	2.9	2.6	50	7.5	2.2	1.5	12.5	3.0	2.9	60	9.0	2.2	1.4	15	3.3	3.0	40	40	6.0	4.4	3.0	10	6.4	5.8	48	14	50	7.5	4.6	3.1	12.5	6.6	6.0	60	9.0	4.4	2.9	15	6.6	6.0	80	12.0	3.8	2.6	20	6.1	5.8	50	50	7.5	6.6	5.0	12.5	10.8	9.7			60	9.0	6.8	4.7	15.0	10.2	9.2
			Catalog No.		外径	長さ	S=Lx15%				S=Lx25%				内径																																																																																																																																																																																																									
					D	L	S	F kN		S	F kN		V	d																																																																																																																																																																																																										
				初回				30万	初回		30万																																																																																																																																																																																																													
			30	30	4.5	1.2	1.1	7.5	2.5	2.4	36																																																																																																																																																																																																													
				40	6.0	2.0	1.3	10	2.9	2.6																																																																																																																																																																																																														
				50	7.5	2.2	1.5	12.5	3.0	2.9																																																																																																																																																																																																														
				60	9.0	2.2	1.4	15	3.3	3.0																																																																																																																																																																																																														
			40	40	6.0	4.4	3.0	10	6.4	5.8	48	14																																																																																																																																																																																																												
				50	7.5	4.6	3.1	12.5	6.6	6.0																																																																																																																																																																																																														
				60	9.0	4.4	2.9	15	6.6	6.0																																																																																																																																																																																																														
				80	12.0	3.8	2.6	20	6.1	5.8																																																																																																																																																																																																														
50	50	7.5	6.6	5.0	12.5	10.8	9.7																																																																																																																																																																																																																	
	60	9.0	6.8	4.7	15.0	10.2	9.2																																																																																																																																																																																																																	
Catalog No.	外径	長さ	S=Lx15%				S=Lx25%				内径																																																																																																																																																																																																													
	D	L	S	F kN		S	F kN		V	d																																																																																																																																																																																																														
				初回	30万		初回	30万																																																																																																																																																																																																																
30	30	4.5	1.2	1.1	7.5	2.5	2.4	36																																																																																																																																																																																																																
	40	6.0	2.0	1.3	10	2.9	2.6																																																																																																																																																																																																																	
	50	7.5	2.2	1.5	12.5	3.0	2.9																																																																																																																																																																																																																	
	60	9.0	2.2	1.4	15	3.3	3.0																																																																																																																																																																																																																	
40	40	6.0	4.4	3.0	10	6.4	5.8	48	14																																																																																																																																																																																																															
	50	7.5	4.6	3.1	12.5	6.6	6.0																																																																																																																																																																																																																	
	60	9.0	4.4	2.9	15	6.6	6.0																																																																																																																																																																																																																	
	80	12.0	3.8	2.6	20	6.1	5.8																																																																																																																																																																																																																	
50	50	7.5	6.6	5.0	12.5	10.8	9.7																																																																																																																																																																																																																	
	60	9.0	6.8	4.7	15.0	10.2	9.2																																																																																																																																																																																																																	