


汎用ガイドブッシュ

ストレートタイプ

BUSH

SOB



●スライド方向



- 相手軸公差
d8：一般用（高負荷）
e7：一般用（軽負荷）
f7：高精度用
- 推奨穴加工公差 H7

〈材質〉SO#50SP2



Order

Catalog No. **SOB** d **19** - D **26** - L **20**

Catalog No.	d	D	L	d	F7	D	m6	適用ワッシャ
	6	10	12	6	+0.022 +0.010	10	+0.015 +0.006	
			8					
			10					
	8	12	12	8		12		—
			15					
			8		+0.028 +0.013			
			10					
	10	14	12	10		14		SOBW10
			15					
		15	10			15	+0.018 +0.007	—
			8					
			10					
SOB			12					
			15					
	12	18	16	12		18		SOBW12
			19					
			20					
			25		+0.034 +0.016			
			30					
			10					
			12					
	13	19	15	13		19	+0.021 +0.008	SOBW13
			16					
			20					
			25					
	14	20	10	14		20		SOBW14


Catalog No.	d	D	L	d	F7	D	m6	適用ワッシャ
			12					
			15					
	14	20	20	14		20		SOBW14
			25					
			30					
			10					
			12					
			15					
	15	21	16	15		21		SOBW15
			20					
			25					
			30					
			10					
			12					
			15					
			16		+0.034 +0.016			
	16	22	19	16		22		SOBW16
			20					
			25					
			30					
SOB			35				+0.021 +0.008	
			40					
	17	23	15	17		23		—
			10					
			12					
			15					
			16					
	18	24	20	18		24		SOBW18
			25					
			30					
			35					
			40					
	19	26	15	19		26		—
			20					
			10					
			12					
			15		+0.041 +0.020			
	20	28	16			28		SOBW20
			19					
			20					
			25					
			30					

汎用ガイドブッシュ

ストレートタイプ

BUSH

SOB



Order

Catalog No. SOB d 35 - D 45 - L 25

Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
		28	35			
		28	40		28	SOBW20
			50			
			10			
			12			
			15			
	20		16	20	+0.021 +0.008	
		30	20		30	—
			25			
			30			
			35			
			40			
			70			
			12			
	22	32	15	22	32	—
			20			
SOB			25	+0.041 +0.020		
			12			
			15			
			16			
			20			
		33	25		33	SOBW25
			30			
	25		35	25	+0.025 +0.009	
			40			
			50			
			60			
			12			
			15			
		35	16		35	—
			20			
			25			
			30			

Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
			35			
	25	35	40	25	35	—
			50			
			20			
	28	38	25	28		SOBW28
			30			
			40			
			12			
			15			
			20		38	
			25			
		38	30		+0.041 +0.020	SOBW30
			35			
			40			
			50			
	30		60	30		
			12			
			15			
			20			
			25			
SOB		40	30		40	+0.025 +0.009
			35			
			40			
			50			
			60			
	31.5	40	30	31.5		—
			40			
			15			
	32	42	20	32	42	—
			30			
			40			
			20			
			25			
			30		+0.050 +0.025	
		44	35		44	SOBW35
			40			
	35		50	35		
			60			
			15			
		45	20		45	—
			25			
			30			


汎用ガイドブッシュ

ストレートタイプ

BUSH

SOB

CAD
FILE



Catalog No. SOB d 50 - D 65 - L 80

Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
			35			
	35	45	40	35	45	—
			50			
			60			
	38	48	30	38	48	—
			40			
			15			
			20			
			25		+0.025 +0.009	
			30			
		50	35		50	SOBW40
			40			
	40		50	40		
			60			
			70			
			80			
SOB			15		+0.050 +0.025	
			25			
			30			
		55	35			—
			40			
			50		55	
			60			
			30			
		55	35		+0.030 +0.011	
			40			
			50			
	45		60	45		SOBW45
			30			
		56	35		56	
			40			
			50			
			60			

Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
			30			
			35			
			40			
	45	60	50	45		—
			60			
			70			
			80			
			20		60	
			30			
			35			
		60	40			
			50			
			60			
			70			
			80	+0.050 +0.025		
			30			
			35			
	50		40	50		SOBW50
		62	50		62	
			60			
SOB			70			
			80		+0.030 +0.011	
			30			
			40			
			50			
		65	60		65	
			70			
			80			
			100			
			30			
			35			
	55	70	40	55	70	SOBW55
			50			
			60			
			70			
			30		+0.060 +0.030	
			35			
			40			
	60	74	50	60	74	SOBW60
			60			
			70			
			80			

ダイガイド部品


汎用ガイドブッシュ

ストレートタイプ

BUSH

SOB

CAD
FILE



Catalog No.

SOB

d

100

D

120

L

120

Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
SOB	60	74	100	60	74	SOBW60
			30			
			35			
			40			
	63	75	50	63	75	SOBW65
			60			
			70			
			80			
	65	80	100	65	80	SOBW70
			60			
			70			
			80			
SOB	70	85	50	70	85	SOBW75
			60			
			70			
			80			
	75	90	100	75	90	SOBW80
			50			
			60			
			70			
	80	95	80	80	95	SOBW85
			90			
			100			
			110			


Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
SOB	75	90	80	75	90	SOBW90
			100			
			60			
			70			
	80	95	80	80	95	SOBW95
			100			
			20			
			40			
	85	100	50	85	100	SOBW100
			60			
			70			
			80			
SOB	90	100	100	90	100	SOBW105
			120			
			140			
			25			
	95	105	60	95	105	SOBW110
			80			
			30			
			50			
	100	110	60	100	110	SOBW115
			70			
			80			
			90			
SOB	105	115	100	105	115	SOBW120
			120			
			140			
			25			
	110	120	60	110	120	SOBW125
			80			
			30			
			50			
	115	125	60	115	125	SOBW130
			70			
			80			
			90			

汎用ガイドブッシュ

ストレートタイプ

BUSH

SOB



Catalog No.

SOB

d

120

D

140

L

100

Catalog No.	d	D	L	d F7	D m6	適用ワッシャ
	100	120	140	100	120	SOBW100
			50			
			70			
	110	130	80	110	130	—
			100			
			120			
			70	+0.071 +0.036		
			80			
	120	140	90	120	140	SOBW120
			100			
			120			
			140			
	125	145	100	125	145	+0.040 +0.015
			120			
			80			
SOB	130	150	100	130	150	
			130			
	140	160	100	140	160	
			140			
			80			
	150	170	100	150	170	+0.083 +0.043
			150			
			80			
	160	180	100	160	180	
			150			
	170	190	100	170	190	
			150			
	180	200	100	180	200	+0.046 +0.017
			150			
	190	210	100	190	210	+0.096 +0.050
			150			
	200	230	150	200	230	
			200			